

# SAFETY DATA SHEET

## 1. Identification

**Product identifier** Textile Marking Texpen® / Dalo® - Orange

**Other means of identification**

**Part Number** 23103, 23106

**Synonyms** FORMULA CODE: \* J3008 (Orange)

**Recommended use** Solvent based marker

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufacturer**

**Company name** ITW Pro Brands

**Address** 805 E. Old 56 Highway  
Olathe, KS 66061

**Country** (U.S.A.)

Tel: +1 800-443-9536

**In Case of Emergency** 1-800-535-5053 (Infotrac)

## 2. Hazard(s) identification

**Physical hazards** Flammable liquids Category 2

**Health hazards** Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Sensitization, skin Category 1

Specific target organ toxicity, single exposure Category 3 narcotic effects

**Environmental hazards** Not classified.

**OSHA defined hazards** Not classified.

**Label elements**



**Signal word** Danger

**Hazard statement** Highly flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.

**Precautionary statement**

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/eye protection/face protection.

**Response** If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish.

**Storage** Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)** None known.

Supplemental information None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	10 - 20
Cyclohexanone		108-94-1	10 - 20
Propylene Glycol Methyl Ether		107-98-2	10 - 20
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin		25068-38-6	0.1 - 1

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth. Get medical attention if symptoms occur.
<b>Most important symptoms/effects, acute and delayed</b>	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Highly flammable liquid and vapor.

### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	--

**Methods and materials for containment and cleaning up**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

**Environmental precautions****7. Handling and storage****Precautions for safe handling**

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities**

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

**8. Exposure controls/personal protection****Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Acetone (CAS 67-64-1)	PEL	2400 mg/m <sup>3</sup>	
		1000 ppm	
Cyclohexanone (CAS 108-94-1)	PEL	200 mg/m <sup>3</sup>	
		50 ppm	
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m <sup>3</sup>	Total dust.

**US. ACGIH Threshold Limit Values**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Cyclohexanone (CAS 108-94-1)	STEL	50 ppm
	TWA	20 ppm
Propylene Glycol Methyl Ether (CAS 107-98-2)	STEL	100 ppm
	TWA	50 ppm
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m <sup>3</sup>

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m <sup>3</sup>
		250 ppm
Cyclohexanone (CAS 108-94-1)	TWA	100 mg/m <sup>3</sup>

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Propylene Glycol Methyl Ether (CAS 107-98-2)	STEL	25 ppm
		540 mg/m <sup>3</sup>
	TWA	150 ppm
360 mg/m <sup>3</sup>		
Silica, amorphous (CAS 7631-86-9)	TWA	100 ppm
		6 mg/m <sup>3</sup>

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
Cyclohexanone (CAS 108-94-1)	80 mg/l	1,2-Cyclohexanediol, with hydrolysis	Urine	*
	8 mg/l	Cyclohexanol, with hydrolysis	Urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines****US - California OELs: Skin designation**

Cyclohexanone (CAS 108-94-1)

Can be absorbed through the skin.

Propylene Glycol Methyl Ether (CAS 107-98-2)

Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

Cyclohexanone (CAS 108-94-1)

Skin designation applies.

**US - Tennessee OELs: Skin designation**

Cyclohexanone (CAS 108-94-1)

Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation**

Cyclohexanone (CAS 108-94-1)

Can be absorbed through the skin.

**US NIOSH Pocket Guide to Chemical Hazards: Skin designation**

Cyclohexanone (CAS 108-94-1)

Can be absorbed through the skin.

**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

If contact is likely, safety glasses with side shields are recommended.

**Skin protection****Hand protection**

Wear appropriate chemical resistant gloves.

**Other**

Wear appropriate chemical resistant clothing.

**Respiratory protection**

In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

**9. Physical and chemical properties****Appearance****Physical state**

Liquid.

**Form**

Liquid.

**Color**

Orange.

**Odor**

Mild. Sweet. Pungent.

<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	131 - 316 °F (55 - 157.78 °C)
<b>Flash point</b>	31.0 °F (-0.6 °C)
<b>Evaporation rate</b>	> 1 (BuAc = 1)
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	> 1 (air = 1)
<b>Relative density</b>	> 1 @ 70°F
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Negligible.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Explosive properties</b>	Not explosive.
<b>Oxidizing properties</b>	Not oxidizing.
<b>VOC</b>	39.74%, 461 g/L

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the decomposition temperature. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong acids. Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Carbon oxides.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes skin irritation. May cause an allergic skin reaction.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical and toxicological characteristics** May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

### Information on toxicological effects

<b>Acute toxicity</b>	Not expected to be acutely toxic.
-----------------------	-----------------------------------

Components	Species	Test Results
Acetone (CAS 67-64-1)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Rat	50 mg/l, 8 Hours
<b>Oral</b>		
LD50	Rat	5800 mg/kg
Cyclohexanone (CAS 108-94-1)		
<b>Acute</b>		
<b>Inhalation</b>		
<i>Vapor</i>		
LC50	Rat	> 6.2 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	1600 mg/kg
Propylene Glycol Methyl Ether (CAS 107-98-2)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rat	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	55 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	> 2000 mg/kg
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (CAS 25068-38-6)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rat	> 800 mg/kg, 24 Hours
<b>Oral</b>		
LD50	Rat	> 500 mg/kg
Silica, amorphous (CAS 7631-86-9)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
<b>Inhalation</b>		
<i>Dust</i>		
LC50	Rat	> 0.14 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	> 3300 mg/kg
Titanium Dioxide (CAS 13463-67-7)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Rat	> 2.3 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	> 2000 mg/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.	
<b>Skin sensitization</b>	May cause an allergic skin reaction.	
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	

**Carcinogenicity** Risk of cancer cannot be excluded with prolonged exposure.

**ACGIH Carcinogens**

Acetone (CAS 67-64-1)	A4 Not classifiable as a human carcinogen.
Cyclohexanone (CAS 108-94-1)	A3 Confirmed animal carcinogen with unknown relevance to humans.
Propylene Glycol Methyl Ether (CAS 107-98-2)	A4 Not classifiable as a human carcinogen.
Titanium Dioxide (CAS 13463-67-7)	A4 Not classifiable as a human carcinogen.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

Cyclohexanone (CAS 108-94-1)	3 Not classifiable as to carcinogenicity to humans.
Silica, amorphous (CAS 7631-86-9)	3 Not classifiable as to carcinogenicity to humans.
Titanium Dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Not listed.

**US. National Toxicology Program (NTP) Report on Carcinogens**

Not listed.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

**Specific target organ toxicity - single exposure** May cause drowsiness or dizziness.

**Specific target organ toxicity - repeated exposure** Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

**12. Ecological information**

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Acetone (CAS 67-64-1)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Cyclohexanone (CAS 108-94-1)			
<b>Aquatic</b>			
Fish	LC50	Fathead minnow (Pimephales promelas)	481 - 578 mg/l, 96 hours
Titanium Dioxide (CAS 13463-67-7)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours

**Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

**Bioaccumulative potential**

**Partition coefficient n-octanol / water (log Kow)**

Acetone	-0.24
Cyclohexanone	0.81

**Mobility in soil** Not established.

**Other adverse effects** None known.

**13. Disposal considerations**

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** D001: Waste Flammable material with a flash point <140 F  
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products**

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging**

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. Transport information**

**DOT**

<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	Paint related material including paint thinning, drying, removing, or reducing compound
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	3
<b>Packing group</b>	II
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	149, B52, IB2, T4, TP1, TP8, TP28
<b>Packaging exceptions</b>	150
<b>Packaging non bulk</b>	173
<b>Packaging bulk</b>	242

**IATA**

<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	Paint related material (including paint thinning or reducing compounds)
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	II
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	3L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.

**IMDG**

<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	II
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>EmS</b>	F-E, S-E
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable.

**DOT**





## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### Toxic Substances Control Act (TSCA)

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Listed.

Cyclohexanone (CAS 108-94-1) Listed.

### SARA 304 Emergency release notification

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SARA 302 Extremely hazardous substance

Not listed.

#### SARA 311/312 Hazardous chemical

Yes

#### Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)  
 Skin corrosion or irritation  
 Serious eye damage or eye irritation  
 Respiratory or skin sensitization  
 Specific target organ toxicity (single or repeated exposure)

#### SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

#### Safe Drinking Water Act (SDWA)

Not regulated.

#### Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

#### Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

#### DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

#### FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Acetone (CAS 67-64-1) Low priority

Cyclohexanone (CAS 108-94-1) Low priority

### US state regulations

#### US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Cyclohexanone (CAS 108-94-1)

Propylene Glycol Methyl Ether (CAS 107-98-2)  
Titanium Dioxide (CAS 13463-67-7)

### California Proposition 65

For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1)  
Propylene Glycol Methyl Ether (CAS 107-98-2)  
Titanium Dioxide (CAS 13463-67-7)

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

**Issue date** 12-15-2020

**Version #** 01

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.